

■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	4200W
Luminous Flux (lm)	3600LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	60pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years



■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	40W
Luminous Flux (lm)	5600LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	60pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years



■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	50W
Luminous Flux (lm)	7000LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	60pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years



■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	60W
Luminous Flux (lm)	8400LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	60pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years

■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	80W
Luminous Flux (lm)	11200LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	120pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years

■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	100W
Luminous Flux (lm)	14000LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	120pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years



■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	120W
Luminous Flux (lm)	16800LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	180pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years



■ Features :



Item	Parameter Range
Material	Die-cast aluminium
CCT	6500K
CRI	≥80Ra
Working lifetime(hours)	50000
Input Voltage	AC100-277V
IP rating	IP65
PF	≥0.95
Power	150W
Luminous Flux (lm)	21000LM
Lamp luminous Efficiency	140lm/W
Condition Temperature	-20~50℃
Work Frequency	50-60HZ
Beam angle	120°
LED Qty	180pcs (Philips/OSRAM)
Temperature group	T6
Explosion-proof grade	Exd IIC T6
Anticorrosion grade	WF2
Surge resistance factor	4KV-6KV
Power supply brand	SAHUNG
Conversion efficiency	93%
Cable inlet	G3/4
Warranty	3years

