Safety Lockout Kit

- a) It is an industrial selection of lockout/tagout devices..
- b) For locking off all kinds of circuit breakers, switches, valve etc.
- c) All items can be easily carried in the lightweight

SL	Item Name	Description	Qty	picture
01	Steel Shackle Padlock	P38S-RED, Shackle Size: 38mmX20mmX6mm, Body Size:37mmX45mmX20mm, Lock Body: Nylon Lock Shackle: Chrome Plated	01	DANGER 45mm ODNOT REMOVE
02	Plastic Shackle Padlock	P38P-RED, Shackle Size: 38mmX20mmX6mm, Body Size:37mmX45mmX20mm, Lock Body: Nylon, Lock Shackle: Nylon PA6	01	DANGER 45mr DO NOT REMOVE
03	Long Steel Shackle Padlock	P76S-RED, Shackle Size: 76mmX20mmX6mm, Body Size:37mmX45mmX20mm, Lock Body: Nylon, Lock Chrome Plated	1	6mm 20mm EE LOCKED OUT DO NOT REMOVE 20mm 37mm



4	Nylon Lockout Hasp	NH01, Overall Size: 44mmX175mm	1	Amm -
5	Nylon Lockout Hasp	NH02, Overall size:41mm×190mm	1	NH02 Overal size 41 mm 190 mm, accept up to 6 padfocks.
6	Nylon Lockout Hasp	NH04, Overall size: 61.5×105mm	1	NH04 Overall size 61.5×105mm, shadle diameter 3mm, accept up to 4 padlocks.
7	Six hole Aluminium HASP	AH11. PA Coated Aluminum Hasp a) Spark resistant aluminum with red nylon coated body. b) Allow multiple padlocks to be used when isolating one energy source c) Lock holes: 3/8" (9.5mm)diameter d) Jaw size: 1.5" (38mm)		
8	Double End Steel HASP	Part No. DSH01 Double-end Steel Lockout Hasp a) Made from red sprayed steel. b) Lock holes: 11mm diameter. c) Allow multiple padlocks to be used when isolating one energy source. d) Overall length: 136mm, with 20.5mm and 46mm jaws.		



9	Portable Lockout Toolbag,	LB02, Material: Nylon Fabrick, Size: 350mm(L)X230mm (H)X210mm(W)		LB02
10	Do Not Operate Lockout Tag (PVC)	Dimension: 75mm (w) X 146mm (H) X 0.5mm (T)	1	Danger Equipment lacked but Do not operate
11	Key Tag	KT01, Made from PE Materials, Durable using, Comes with a writable paper.	1	
12	Pen for tag	ITP 01,These special pens are designed for writing on lockout tags. The ink is waterproof and each pen has an eraser on the end so tags can easily be used more than once. The pens are black.	1	
13	Circuit Breaker Lockout	POS, (Pin Out Standard), 2 holes required, fit up to 60Amp	1	7.5mm 7.5mm POS



14	tie bar lockout	TBLO, (Tie Bar Lockout), no hole in breakers required. Made of a durable glass-filled nylon. Available for single and multi-pole breakers.	1	TBLO
15	Circuit Breaker Lockout,	CBL01-2, lock hole:9mm., max clamping 8mm, without installing tools needed.Material: Nylon PA.	1	Ф9mm 8mm СВL01-2
16	Circuit Breaker Lockout,	CBL02-3. lock hole:10mm, max clamping 10.5mm, without installing tools needed.	1	Ф9mm 10mm
17	MCB & MCCB Lockout	ICL-06, Can accommodate one safety padlock with shackle diameter <= 7mm. made from rugged reinforced nylon PA. Can lock it with screw driver. can lock all kinds of circuit breaker	1	



18	MCB & MCCB Lockout	ICL-06, Can accommodate one safety padlock with shackle diameter <= 7mm. made from rugged reinforced nylon PA. Can lock it with screw driver. can lock all kinds of circuit breaker	1	
19	Circuit Breaker Lockout,	GCBL01, the length of the rod is 195mm. Material: Plastic ABS & Nylon PA.	1	
20	Circuit Breaker Lockout,	CBL11, For 120-277V breaker lockouts, handle width <18mm, comes with a cleat. Made of rugged polypropylene and impact modified nylon. Accepts lock shackles up to 9/32" (7mm)in diameter.	1	
21	Circuit Breaker Lockout,	CBL12, For 480-600V breaker lockouts, handle width <42mm, comes with a cleat. Made of rugged polypropylene and impact modified nylon. Accepts lock shackles up to 9/32" (7mm)in diameter.	1	



22	Circuit Breaker Lockout,	CBL13. For Large 480-600V breaker lockouts, handle width <72mm. Made of rugged polypropylene and impact modified nylon. Accepts lock shackles up to 9/32" (7mm)in diameter.	1	
23	Power Handle Lockout	PHL01. It consists of a orange base (with 3M glue), two adjusters and a red belt. Made of durable industrial ABS, withstand temperature from - 20°C-90°C.	1	Red belt:280mm(L) ×25mm(W) 48mm 43.6mm
24	Electrical Plug Lockout	EPL01. Dimension: 51mm (height) x 51mm(thick)x89mm(width). Made of rugged ABS. For 220V plugs	1	Control Registration of the Control
25	Electrical Plug Lockout	EPL01M. 65mm (height) x 65mm(thick)x118mm(width) .For 220V plugs.	1	To Marketon
26	Electrical Plug Lockout	EPL02. 82mm (height) x 83mm(thick)x178mm(width). For large 220V/500V plugs	1	Children in the state of the st



27	Universal Valve Lockout	UVL01. Made of industrial grade steel and nylon. Withstand temperature from – 20C to 80C. resistance of chemical, Extreme temperatures and UV rays.	1	
28	Cable Lockout	CB01-4. Cable diameter 4mm, length 2 m. Lock body: made of ABS, withstands chemicals. Cable: tough, flexible multi-stranded steel cable, with clear plastic insulation coating.	1	DANGER DO NOT OPERATE
29	Cable Lockout	ICAL-08. Cable Diameter 4.8mm & length: 1.8m. Lock body made of ABS. Withstand temperature from – 20C to 80C.	1	
30	Cylinder Tank Lockout,	Part No.: ASL04 Air Source Lockout a) Made from engineering plastic ABS. b) Prevents access to the main cylinder valve. c) Accommodates neck rings up to 35mm, and max diameter inside 83mm. d) Easy and efficient installation to save you time. e) Can be locked with 3 padlocks, lock shackle diameter up to 8.5mm.	1	POWER CORD LOCKED OUT This how holds derich may only pa tempoyed by: The start of the start
31	Air Source Lockout	Part No.: IAL-02 Air Source Lockout, Diameter: 196mm (L) X 35mm (W) X 3mm (T). Easy to install Made from 304 Stainless steel	1	A Contract of



32	Ball Vavle Lockout, (DN8- DN50),	Part No.: ABVL01 SmallAdjustable Ball valve lockout a) Made from durable ABS, highly resistant to cracking and abrasion, resistant to extreme weather temperature conditions. b) The two halves of the lockout encompass the ball valve handle to secure it from inadvertent activation of the valve. c) Can beequipped together with padlocks. Padlock locked shackle max diameter is 9mm.	1	
33	Gate Valve, 1" to 6 1/2" in diameter	d) Suitable for pipes 1/2" to 2.5" in diameter,OPEN on pipes from 1/2" to 1.25" AGVL01 Adjustable Gate Valve Lockout, Suitable for valve handle 1" to 6 1/2" in diameter a) Made from durable ABS, withstand temperature from - 20°C to +90°C. b) Can be equipped together with padlocks. Padlock locking shackle max diameter 3/8" (9.8mm). c) Can be covered and rotated freely around valve wheel, and adjustable to fit a range of valve handles.	1	LOCKED OUT REMOVE
34	Universal Valve Lockout	UVL01. Made of industrial grade steel and nylon. Withstand temperature from – 20C to 80C. resistance of chemical, Extreme temperatures and UV rays.	1	

